



(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
13.01.1999 Bulletin 1999/02

(51) Int Cl.<sup>6</sup>: **B60C 11/12**, B60C 11/04,  
B60C 9/20  
// B60C115:00, B60C111:00

(21) Application number: 98304631.9

(22) Date of filing: 11.06.1998

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU**  
**MC NL PT SE**  
 Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventor: Himuro, Yasuo  
Tachikawa-City, Tokyo (JP)

(74) Representative: **Whalley, Kevin**  
**MARKS & CLERK,**  
**57-60 Lincoln's Inn Fields**  
**London WC2A 3LS (GB)**

(30) Priority: 08.07.1997 JP 182597/97


(71) Applicant: **Bridgestone Corporation**  
**Tokyo (JP)**

(54) All-season pneumatic radial tire for passenger car

(57) An all-season pneumatic radial tire has a block pattern in a tread defined by two circumferential main grooves (1) and slant grooves, in which the two circumferential main grooves are arranged on either side of the tread with respect to a pattern center to divide the tread into a central region (TC) and side regions (TS). In this tire, the slant grooves are comprised of steep slant groove segments (2) and gentle slant groove segments (3), and the steep slant groove segments (2) are disposed in the central region (TC) and the gentle slant

groove segments (3) are disposed in both side regions (TS) of the tread in a herringbone directional tread pattern designating a rotating direction (RD) of the tire to be mounted onto a vehicle. A surface of an acute corner angle zone of each of the blocks (4) defined by the circumferential main grooves (1) and the steep slant groove segments (2) and arranged in the central region (TC) of the tread is chamfered over a distance of 10-30 mm from a taper end in a longitudinal direction so as to gradually shallow from the taper end toward a thickened zone.

**FIG. 1**



## Description

This invention relates to a pneumatic radial tire, particularly an all-season pneumatic radial tire for passenger cars.

As shown in Fig. 2, the conventionally typical all-season pneumatic radial tire for passenger car has a tread pattern wherein a circumferential groove extends substantially in a straight line in a central portion of a tread (or so-called center groove) and plural circumferential grooves extending straightforward or zigzag in the circumferential direction are arranged on either side of the center groove and many blocks are formed at intervals in axial and circumferential directions of the tire by these circumferential grooves with lateral grooves arranged at an interval in the circumferential direction so as to cross the tread.

Such an all-season pneumatic radial tire is required to have various performances such as drainage performance in the running on a wet road surface, low noise, steering stability in the running on a dry road surface, braking traction, straight running and cornering performances in the running on snow, braking performance on ice and the like.

Recently it is demanded to develop all-season pneumatic radial tires having excellent drainage performance in the running on the wet road surface and noise reduction without remarkably sacrificing the steering stability in the running on the dry road surface, performances on snow, braking performance on ice and the like of the tire.

It is therefore an object of the invention to provide an all-season pneumatic radial tire for passenger car having excellent drainage performance in the running on the wet road surface and noise reduction without degrading various performances of the conventional all-season pneumatic radial tire, particularly the steering stability in the running on the dry road surface, performances on snow and braking performance on ice.

According to the invention, there is the provision of an all-season pneumatic radial tire comprising a tread of a block pattern defined by two circumferential main grooves arranged at a given interval in an axial direction of the tire and continuously extending in a circumferential direction of the tire and many slant grooves arranged at a given interval in the circumferential direction of the tire and extending obliquely with respect to the circumferential direction of the tire, in which the two circumferential main grooves are arranged on either side of the tread with respect to a pattern center to divide the tread into a central region located between the two circumferential main grooves and having a width corresponding to about 15%-45% of a tread width and both side regions each located between the circumferential main groove and an end of the tread, the improvement wherein (1) the slant groove is comprised of a steep slant groove segment extending at a relatively small inclination angle with respect to the circumferential direction and a gentle

slant groove segment extending at a relatively large inclination angle with respect to the circumferential direction; (2) the steep slant groove segment is disposed in the central region of the tread and extends substantially in a straight line from an end of the groove segment opening to the circumferential main groove toward the other end opening to the other circumferential main groove; (3) the gentle slant groove segment is disposed in each of both side regions of the tread and extend so as to gradually increase the inclination angle with respect to the circumferential direction from an inner end of the groove segment opening to the circumferential main groove toward an outer end thereof opening to the tread end; (4) the gentle slant groove segment located in one of both side regions of the tread and the gentle slant groove segment located at the other side region are arranged in a herringbone form in pairs to form a directional tread pattern designating a rotating direction of the tire to be mounted onto a vehicle that a portion of a block defined between the gentle slant groove segments neat to a side of an equatorial plane of the tire precedently contacts with ground and a portion of the block located apart away from the equatorial plane succeedingly contacts with the ground in which the arrangement of the gentle slant groove segments located at one of both side regions is shifted by a half pitch to the arrangement of the gentle slant groove segments located at the other side region; and (5) a surface of an acute angle corner zone of each of the blocks defined by the circumferential main grooves and the steep slant groove segments and arranged in the central region of the tread is chamfered over a distance of 10-30 mm from a taper end in a longitudinal direction so as to gradually shallow from the taper end toward a thickened zone.

In a preferable embodiment of the invention, the steep slant groove segment extends at an inclination angle of 10-45° with respect to the circumferential direction and the gentle slant groove segment extends at an inclination angle of 30-90° with respect to the circumferential direction.

In another preferable embodiment of the invention, each of the blocks is provided with a plurality of sipes each extending at a relatively large inclination angle of 70-90° with respect to the circumferential direction and opening at its end to the circumferential main groove or the tread end.

In the other preferable embodiment of the invention, the number of the steep slant groove segments is not more than a half of the number of the gentle slant groove segments so as to make an interval between the steep slant groove segments in the circumferential direction not less than two times an interval between the gentle slant groove segments in the radial direction, and each of the blocks arranged in the central region of the tread is a parallelogram having a relatively large circumferential component as compared with each of the blocks arranged in both side regions of the tread.

In a still further preferable embodiment of the inven-

tion, the tire is provided with a belt comprised of at least two rubberized cord layers each containing cords arranged in parallel to each other at a cord angle of about 10-30° with respect to the circumferential direction of the tire, cords of which layers being crossed with each other with respect to an equator of the tire, and the extending direction of the cord in an outermost layer of the belt in the radial direction is crossed with the extending direction of the steep slant groove segment with respect to the equator of the tire.

In the other preferable embodiment of the invention, a surface of an acute angle corner zone of each of the blocks arranged in both side regions and defined between the circumferential main groove and the gentle slant groove segment is chamfered over a distance of 10-30 mm from a taper end in a longitudinal direction so as to gradually shallow from the taper end toward a thickened zone.

The pneumatic radial tire according to the invention has the aforementioned structure, and particularly forms a row of many blocks arranged at intervals in the circumferential direction of the tire in the central region of the tread, so that the rigidity in the central region of the tread becomes higher as compared with the tire having the center groove and hence the steering stability in the running on dry road surface, wet road surface and on snow is improved.

In the pneumatic radial tire according to the invention, the two circumferential main grooves continuously extending in the circumferential direction of the tire are arranged adjacent to either side of the block row formed in the central region of the tread, so that there is obtained an excellent drainage performance in the running on the wet road surface or excellent resistance to hydroplaning.

In the pneumatic radial tire according to the invention, a plurality of the steep slant groove segments are disposed in the central region of the tread, the shearing force of snow column through a lug component can be obtained without lowering the rigidity in the circumferential direction to establish the performance on snow and the performance on ice. In this case, the steep slant groove segments disposed in the central region of the tread extend at a relatively small inclination angle of, preferably 10-45° with respect to the circumferential direction, so that it is possible to smoothly conduct the drainage between the two circumferential main grooves to improve the drainage performance of the tire and also impact component of the tire is decreased to reduce the noise of the tire.

When the inclination angle of the steep slant groove segment exceeds 45° with respect to the circumferential direction, the branching and joining of water flow become difficult to degrade the drainage performance of the tire and also the rigidity of the block row in the circumferential direction is lowered to degrade the braking performance of the tire on ice. While, when it is less than 10°, the shearing force of snow column effective for the

traction is not obtained, and also it is required that a pitch length between substantially parallelogrammatic blocks defined by the steep slant groove segments and the two circumferential main grooves is made large in order to ensure the distance between the steep slant groove segments in the axial direction of the tire and hence the pattern noise is degraded.

In the pneumatic radial tire according to the invention, the surface of the acute angle corner zone of each of the blocks defined by the circumferential main grooves and the steep slant groove segments and arranged in the central region of the tread is chamfered over a distance of 10-30 mm from the taper end of the block in the longitudinal direction thereof so as to gradually shallow from the taper end of the block toward the thickened zone thereof, so that the drainage performance in the running on the wet road surface or the resistance to hydroplaning is improved while ensuring the rigidity of the block.

In the pneumatic radial tire according to the invention, each of the blocks formed in the central region and both side regions of the tread is provided with a plurality of sipes each extending at a relatively large inclination angle of 70-90° with respect to the circumferential direction and opening at its end to the circumferential main groove or the tread end, whereby friction coefficient on ice through an edge effect of the sipe is increased to ensure the braking performance of the tire on ice.

Moreover, it is favorable that the sipe density in the block located at the outermost side of the tread in the widthwise direction is set to a low level among the blocks formed in the central region and both side regions of the tread in order to ensure the steering stability of the tire.

In the pneumatic radial tire according to the invention, the gentle slant groove segments extending at a relatively large inclination angle of 30-90° with respect to the circumferential direction are disposed in both sides of the tread between the circumferential main groove and the tread end and extend so as to gradually increase the inclination angle with respect to the circumferential direction from an inner end of the groove segment opening to the circumferential main groove toward an outer end thereof opening to the tread end, so that the drainage from the circumferential main groove toward the tread end is smoothly conducted to improve the drainage performance of the tire in the running on the wet road surface or the resistance to hydroplaning. Since the gentle slant groove segment is extended smoothly as mentioned above, a large shearing force is obtained by forming a strong snow column to improve a traction performance on snow.

In the pneumatic radial tire according to the invention, the gentle slant groove segment located in one of both side regions of the tread and the gentle slant groove segment located at the other side region are arranged in a herringbone form in pairs to form a directional tread pattern designating a rotating direction of the tire to be mounted onto a vehicle that a portion of a

block defined between the gentle slant groove segments neat to a side of an equatorial plane of the tire precedently contacts with ground and a portion of the block located apart away from the equatorial plane succeedingly contacts with the ground in which the arrangement of the gentle slant groove segments located at one of both side regions is shifted by a half pitch to the arrangement of the gentle slant groove segments located at the other side region as previously mentioned, whereby the tire noise is reduced.

The invention will be described with reference to the accompanying drawings, wherein:

Fig. 1 is a partly enlarged plane view of an embodiment of the tread pattern in the tire according to the invention; and

Fig. 2 is a partly enlarged plane view of a tread pattern in the conventional tire.

In Figs. 1 and 2, the tire has a tire size of 195/65R15 and a tread width TW of 146 mm.

The tire shown in Fig. 1 has a tread pattern comprising many blocks 4, 5 defined by two circumferential main grooves 1 arranged at a given interval in an axial direction of the tire and continuously extending in a circumferential direction of the tire and many slant grooves arranged at a given interval in the circumferential direction of the tire and extending obliquely with respect to the circumferential direction of the tire.

By arranging the two circumferential main grooves 1 on either side of the tread with respect to a pattern center is divided the tread into a central region TC located between the circumferential main grooves 1 and having a width corresponding to 25% of a tread width TW and both side regions TS each located between the circumferential main groove 1 and a tread end TE.

The slant groove is comprised of a steep slant groove segment 2 extending a relatively small inclination angle, e.g. an angle of 20° with respect to the circumferential direction and a gentle slant groove segment 3 extending at a relatively large inclination angle, e.g. angle of 40-85° with respect to the circumferential direction.

The steep slant groove segment 2 is disposed in the central region TC of the tread and extends substantially in a straight line from an end opening to the circumferential main groove 1 toward the other end facing to the other circumferential main groove 1.

The gentle slant groove segment 3 is disposed in each side region TS of the tread and extends from an end facing to the circumferential main groove 1 toward an outer end facing to the tread end TE so as to gradually increase the inclination angle from about 40° to about 85°.

The gentle slant groove segment 3 located in one of both side regions TS of the tread and the gentle slant groove segment 3 located at the other side region are arranged in a herringbone form in pairs to form a direc-

tional tread pattern designating a rotating direction RD (forward direction) of the tire to be mounted onto a vehicle that a portion of a block defined between the gentle slant groove segments neat to a side of an equatorial plane of the tire precedently contacts with ground and a portion of the block located apart away from the equatorial plane succeedingly contacts with the ground, in which the arrangement of the gentle slant groove segments 3 located at one of both side regions is shifted by a half pitch to the arrangement of the gentle slant groove segments 3 located at the other side region.

The surface of an acute angle corner zone of each of the blocks 4 defined by the circumferential main grooves 1 and the steep slant groove segments 2 and arranged in the central region TC of the tread is chamfered over a distance of 25 mm at a stepping-in side and a distance of 15 mm at a kicking-out side from a taper end in a longitudinal direction so as to gradually shallow from the taper end toward a thickened zone.

The surface of an acute angle corner zone of each of the blocks 51 arranged in both side regions TS and defined between the circumferential main groove 1 and the gentle slant groove segment 3 is chamfered over a distance of 15 mm from a taper end in a longitudinal direction so as to gradually shallow from the taper end toward a thickened zone.

Each of the blocks 4, 5 (51, 52) is provided with a plurality of sipes 6, 7 (71, 72) each opening at its end to the circumferential main groove 1 or the tread end TE. The sipe 6 disposed in the block 4 extends at an inclination angle of 90° with respect to the circumferential direction, and the sipe 71 disposed in the block 51 extends at an inclination angle of 70° with respect to the circumferential direction, and the sipe 72 disposed in the block 52 extends at an inclination angle of 80° with respect to the circumferential direction.

The number of the steep slant groove segments 2 is a half of the number of the gentle slant groove segments 3 so as to make an interval between the steep slant groove segments 2 in the circumferential direction two times an interval between the gentle slant groove segments 3 in the radial direction, and each of the blocks 4 arranged in the central region TC of the tread is a parallelogram having a relatively large circumferential component as compared with each of the blocks 5 arranged in both side regions TS of the tread.

The tire of the illustrated embodiment is provided at its inside with a belt comprised of two rubberized cord layers each containing cords arranged in parallel to each other at a cord angle of 20° with respect to the circumferential direction of the tire, cords of which layers being crossed with each other with respect to an equator of the tire. The extending direction of steel cord in an outermost layer of the belt in the radial direction is crossed with the extending direction of the steep slant groove segment 2 with respect to the equator of the tire.

The conventional tire shown in Fig. 2 has a tread pattern that a circumferential groove extending substan-

tially in a straight line in the center region of the tread (which is so-called center groove) and two circumferential grooves extending zigzag in the circumferential direction are arranged on either side of the center groove and two circumferential grooves extending in a straight line in the circumferential direction are arranged at the outside thereof to form many blocks arranged at given intervals in the axial direction and circumferential direction of the tire together with many lateral grooves extending in a direction crossing the tread.

The tests for evaluating the drainage performance in the running on wet road surface, noise level of the tire, steering stability in the running on dry road surface, performances on snow and braking performance on ice are carried out with respect to the tire according to the invention and the conventional tire.

The drainage performance in the running on wet road surface is evaluated by a driver's feeling on a limit speed causing hydroplaning during the running on a wet road surface having a water depth of 5 mm. The steering stability in the running on dry road surface is evaluated by a driver's feeling when sport running is carried out on a circuit course of dry state under various running modes. The performances on snow are evaluated by a driver's total feeling on braking performance, traction performance, straight running performance and cornering performance on a test course of pressed snow state. The braking performance on ice is evaluated by a stopping distance when the vehicle is fully braked from a running state at a speed of 20 km/h on an iced course.

As a result of the above evaluation tests, when each performance is represented by an index on the basis that the conventional tire is 100 (the larger the index value, the better the performance), in the tire according to the invention, the steering stability on dry road surface is 105, and the performances on snow are 105, and the braking performance on ice is 110, and the drainage performance on wet road surface and the noise level are 120, respectively. That is, the tire according to the invention is superior in all of the above performances to the conventional tire.

As seen from the above, according to the invention, there can be provided an all-season pneumatic radial tire having excellent drainage performance in the running on wet road surface and noise level without degrading the steering stability in the running on dry road surface, the performances on snow and the braking performance on ice.

## Claims

1. A pneumatic radial tire comprising a tread having a block pattern defined by two circumferential main grooves (1) arranged at a given interval in the axial direction of the tire and continuously extending in the circumferential direction of the tire and slant grooves arranged at given intervals in the circum-

ferential direction of the tire and extending obliquely with respect to the circumferential direction of the tire, in which the two circumferential main grooves (1) are arranged on either side of the tread with respect to the pattern center to divide the tread into a central region (TC) located between the two circumferential main grooves and having a width corresponding to about 15%-45% of the tread width (TW) and both side regions (TS) each located between a circumferential main groove and an end (TE) of the tread, characterized in that (i) the slant grooves are comprised of steep slant groove segments (2) extending at a relatively small inclination angle with respect to the circumferential direction and gentle slant groove segments (3) extending at a relatively large inclination angle with respect to the circumferential direction; (ii) the steep slant groove segments (2) are disposed in the central region (TC) of the tread and extend substantially in a straight line from one end of the groove segment opening to one circumferential main groove (1) toward the other end opening to the other circumferential main groove; (iii) the gentle slant groove segments (3) are disposed in each of both side regions (TS) of the tread and extend so as to gradually increase the inclination angle thereof with respect to the circumferential direction from an inner end of the groove segment opening to a circumferential main groove (1) toward an outer end thereof opening to the tread end (TE); (iv) the gentle slant groove segments located in one of both side regions (TS) of the tread and the gentle slant groove segments located in the other side region (TS) are arranged in a herringbone directional tread pattern designating a rotating direction (RD) of the tire to be mounted onto a vehicle such that a portion of a block (5) defined between the gentle slant groove segments (3) and located nearer to the equatorial plane of the tire precedently contacts with the ground and a portion of the said block located further from the equatorial plane succeeding-ly contacts with the ground, in which the arrangement of the gentle slant groove segments located at one of both side regions is shifted by a half pitch with respect to the arrangement of the gentle slant groove segments located at the other side region; and (v) a surface of an acute angle corner zone of each of the blocks (4) defined by the circumferential main grooves (1) and the steep slant groove segments (2) and arranged in the central region (TC) of the tread is chamfered over a distance of 10-30 mm from a taper end in a longitudinal direction so as to gradually shallow from the taper end toward a thickened zone.


2. A pneumatic radial tire as claimed in claim 1, characterized in that the steep slant groove segments (2) extend at an inclination angle of 10-45° with respect to the circumferential direction, and the gentle

slant groove segments (3) extend at an inclination angle of 30-90° with respect to the circumferential direction.


3. A pneumatic radial tire as claimed in claim 1 or 2, 5  
characterized in that each of the blocks (4;5) is provided with a plurality of sipes (6;7) each extending at a relatively large inclination angle of 70-90° with respect to the circumferential direction and opening at its end to a circumferential main groove (1) or a tread end (TE). 10
4. A pneumatic radial tire as claimed in any of claims 1 to 3, 15  
characterized in that the number of the steep slant groove segments (2) is not more than half of the number of the gentle slant groove segments (3) so as to make the interval between the steep slant groove segments in the circumferential direction not less than two times the interval between the gentle slant groove segments in the radial direction, and each of the blocks (4) arranged in the central region (TC) of the tread is a parallelogram having a relatively large circumferential component as compared with each of the blocks (5) arranged in both side regions (TS) of the tread. 20 25
5. A pneumatic radial tire as claimed in any of claims 1 to 4, 30  
characterized in that the tire is provided with a belt comprised of at least two rubberized cord layers each containing cords arranged in parallel to each other at a cord angle of about 10-30° with respect to the circumferential direction of the tire, cords of which layers being crossed with each other with respect to an equator of the tire, and the extending direction of the cord in an outermost layer of the belt in the radial direction is crossed with the extending direction of the steep slant groove segments (2) with respect to the equator of the tire. 35 40
6. A pneumatic radial tire as claimed in any of claims 1 to 5, 45  
characterized in that a surface of an acute angle corner zone of each of the blocks (5) arranged in both side regions (TS) and defined between the circumferential main groove (1) and the gentle slant groove segments (3) is chamfered over a distance of 10-30 mm from a taper end in a longitudinal direction so as to gradually shallow from the taper end toward a thickened zone. 50

55

**FIG. 1**



**FIG. 2**  
PRIOR ART





(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 890 456 A3**

(12)

**EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
15.12.1999 Bulletin 1999/50

(51) Int Cl.<sup>6</sup>: **B60C 11/12, B60C 11/04,  
B60C 9/20, B60C 11/13  
// B60C115:00, B60C111:00**

(43) Date of publication A2:  
13.01.1999 Bulletin 1999/02

(21) Application number: **98304631.9**

(22) Date of filing: **11.06.1998**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventor: **Himuro, Yasuo**  
**Tachikawa-City, Tokyo (JP)**


(74) Representative: **Whalley, Kevin**  
**MARKS & CLERK,**  
**57-60 Lincoln's Inn Fields**  
**London WC2A 3LS (GB)**

(30) Priority: **08.07.1997 JP 18259797**

(71) Applicant: **Bridgestone Corporation**  
**Tokyo (JP)**

(54) **All-season pneumatic radial tire for passenger car**

(57) An all-season pneumatic radial tire has a block pattern in a tread defined by two circumferential main grooves (1) and slant grooves, in which the two circumferential main grooves are arranged on either side of the tread with respect to a pattern center to divide the tread into a central region (TC) and side regions (TS). In this tire, the slant grooves are comprised of steep slant groove segments (2) and gentle slant groove segments (3), and the steep slant groove segments (2) are disposed in the central region (TC) and the gentle slant groove segments (3) are disposed in both side regions (TS) of the tread in a herringbone directional tread pattern designating a rotating direction (RD) of the tire to be mounted onto a vehicle. A surface of an acute corner angle zone of each of the blocks (4) defined by the circumferential main grooves (1) and the steep slant groove segments (2) and arranged in the central region (TC) of the tread is chamfered over a distance of 10-30 mm from a taper end in a longitudinal direction so as to gradually shallow from the taper end toward a thickened zone.





European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 98 30 4631

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	PATENT ABSTRACTS OF JAPAN vol. 018, no. 274 (M-1611), 25 May 1994 (1994-05-25) & JP 06 048120 A (BRIDGESTONE CORP), 22 February 1994 (1994-02-22) * abstract *	1,2	B60C11/12 B60C11/04 B60C9/20 B60C11/13 //B60C115:00, B60C111:00
A	US 5 329 980 A (SWIFT DOUGLAS A ET AL) 19 July 1994 (1994-07-19)	1,2	
A	EP 0 715 973 A (BRIDGESTONE CORP) 12 June 1996 (1996-06-12)	1,3	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			B60C
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>20 October 1999</b>	Examiner <b>Baradat, J-L</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application C : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 (01/92) (P/M/C/1)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 30 4631

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

20-10-1999

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
JP 06048120	A	22-02-1994	NONE	
US 5329980	A	19-07-1994	NONE	
EP 0715973	A	12-06-1996	JP 8156525 A	18-06-1996
			CA 2164580 A	08-06-1996
			DE 69511514 D	23-09-1999
			US 5785780 A	28-07-1998

EPO FORM 10459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**THIS PAGE BLANK (USPTO)**